

Product News

New AS1 and DS1 trimmer adjustment

Datasensor UK introduces new models of the AS1/DS1 series with adjustment trimmer, this product range enlargement allows us to cover more market needs, especially where a narrow beam or short operating distance is required ...

[>> read article](#)

[>> click for AS1 datasheet](#)

[>> click for DS1 datasheet](#)



SG-IP69K: PMMA tubular enclosure for IP69K protection

Datasensor UK presents the new PMMA TUBULAR ENCLOSURE FOR IP69K PROTECTION ACCESSORY, **SG-IP69K** series.

SG-IP69K accessory is a PMMA acrylic tube used to protect and seal the safety light curtains of SG2, SG4 and SG BODY COMPACT series. Thanks to SG-IP69K accessory the IP protection of the safety light curtain inside is increased from IP65 to IP67, IP68 and IP69K ...

[>> read article](#)

[>> click for datasheet](#)



SE4-T/L muting: new models with through beam Muting arms

Datesensor UK is proud to announce that the SE4-T/L MUTING series has been enlarged.

The safety light curtains of the SE4T-L MUTING series satisfy all applications that require the Muting function, thanks to the use of pre-assembled, pre-cabled and pre-aligned Muting sensors ...

[>> read article](#)

[>> click for datasheet](#)

United States postal service chooses Datalogic Automation

After an extensive competition between the top scanning companies in the world, the United States Postal Service® selected Datalogic Automation as its provider for the next generation of barcode scanning equipment. Datalogic Automation's Matrix 400™ imager will be used in material handling systems that process letter trays and flat tubs ...

[>> read article](#)



New DS4800 models and accessories: model with integrated oscillating mirror and GFC-40 105° Deflection Mirror

With the **DS4800 OM** version and new **GFC-40 105°** deflection mirror accessory, Datalogic Automation extends its product portfolio completing the 4000 family designed for the **Factory Automation** market, and in particular for shop floor and automatic warehousing applications.

DS4800 OM is a complementary model necessary in all cases where the linear barcode has picket fence orientation and a multiple parallel beam is necessary to intersect the barcode itself.

The features of the **DS4800 OM** model are at the top of its category in terms of scan frequency, mechanical dimensions and dynamic software control.

The new **GFC-40 105°** deflection mirror accessory mounted on the DS4800 linear model presents a different form factor thanks to its lateral output window. This feature, together with the embedded 105° laser beam deflection angle, is very useful for installations with mechanical constraints.

[>> click for datasheet](#)



For More Information: